



Taping Equipment Comparison Chart

	TM-50	TM-50 XL	TM-50 OEM	TM-400	TM-500	The Hawk
COMPONENT INPUT						
Manual	X	X	AD			
Automatic			AD	X	X	X
PICK HEAD TYPE						
Linear				X	X	
Rotary						X
INPUT OPTIONS						
Bowl			AD	X	X	X
Tray			AD	X	X	
Tube			AD	X	X	
Tape			AD	X	X	
OUTPUT OPTIONS						
Tray					X	
Tape	X	X	X	X	X	X
TAPE WIDTHS (mm)						
	8-72	8-120	8-56	8-72	8-56	8-24
MAX UNITS/HR						
	AD	AD	AD	3,500	4,500	22,000
PART MARKING						
					OP	OP
VISION						
Top Side (Mark/Pin 1)	OP	OP	OP	X	OP	OP
Bottom Side					OP	OP
Lead Inspection (2D)	OP	OP	OP		OP	
Lead Inspection (3D)					OP	
5 Sided (Bottom & 4 Sides)					OP	OP
SENSOR PACKAGE*						
	OP	X	X	X		X
PART ROTATION						
				± 90°	± 180°	OP
AUTOMATIC TESTING						
	NA	NA	NA	NA	OP	OP

OP= Optional AD= Application Dependent NA= Not Applicable Note: All machines accommodate heat activated and pressure sensitive cover tape
 *Sensor Package includes all or some of the following: Empty Pocket Detection, Low Cover Sensor, Low Carrier Sensor, Carrier Motion, Vision, Jam In Track